



At a Glance



3x

Ethernet WAN (Gigabit Ethernet)



3x

Ethernet LAN (Gigabit Ethernet)



1x

USB WAN Port



1Gbps

Stateful Firewall Throughput



150Mbps

PepVPN Throughput (256-bit AES)



Up to 100

VPN Peers

Specifications Power Input LCD Console 2x USB 2x LAN Bypass Ports Power Switch 3x 10/100/1000M 3x 10/100/1000M

WAN Interface	3 (GE) 1x USB Interface	Remote AP & Multiple Config Profiles Management	Yes
LAN Interface	3 (GE)	LAN Bypass	Yes
Stateful Firewall Throughput	1 Gbps	Remote User Access	Yes
PepVPN Throughput (No Encryption)	150 Mbps	L2TP / PPTP VPN Server	Yes
PepVPN Throughput	150 Mbps	Bandwidth Usage Monitor	Yes
(256-bit AES)	100 Mbpc	QoS for VoIP and E-commerce	Yes
Recommended Users	50 - 500		
Number of PepVPN SpeedFusion Peers	30/1001	User Groups Bandwidth Control	Yes
Maximum Number	50	Web Blocking	Yes
of AP Supported	50	Operating Temperature	32°- 104° F / 0°- 40° C
SpeedFusion Hot Failover	Yes	LACP (802.3ad) NIC Bonding	Yes
SpeedFusion WAN Smoothing	Yes	Power Consumption	50 W
SpeedFusion Bandwidth Bonding	Yes	1U Rack-mount	Yes
Central Management	InControl 2	Dimensions (W x D x H)	16.8 x 12 x 1.73 inches / 42.6 x 30.5 x 4.4 cm
High Availability	Yes	Weight	8.8 pounds / 4 kg
Drop-in Mode	Yes	Certifications	FCC, CE, RoHS
Content Filtering	Full	Warranty	1-Year Limited Warranty
Manage Pepwave AP	Yes	Package Content	1x Balance 380 Power Cord (ACW-614) 1 Pair of Mounting Brackets (ACW-382)

¹30 SpeedFusion Peers are enabled by default. 100 Peers can be activated with additional license (SFN-LC-100).

Ordering Information

Product Code	Model	Description
BPL-380	Balance 380	3x GE WAN ports and 3x GE LAN ports. SpeedFusion capable.

Accessories

Product Code	Description
SFN-LC-100	Enable up to 100 SpeedFusion peers.

Ethernet WAN

Ethernet LAN